

Easily Unpack Servers from Boxes

LE-Series Lift Extensions



Never manually unpack boxes and lift equipment again. The ServerLIFT LE-500X® and LE-1000X® Lift Extensions safely lift and remove servers, switches, UPS devices, and other rack-mounted equipment out of crates and boxes without destroying the packaging or straining your back.

The heavy-duty slings simply feed under the server or switch in the box and attach to the Lift Extension, allowing the ServerLIFT® unit to raise the server up so you can remove the packaging without hassle.

LE-Series Model	Max. Load Rating	Compatibility
LE-500X	500 lb (227 kg)	SL-500X [®] , SL-350X [®]
LE-1000X	700 lb (318 kg)	SL-1000X [®]

The LE-500X Lift Extension works with any ServerLIFT SL-500X® or SL-350X® lift, while the LE-1000X® Lift Extension is compatible with the ServerLIFT® SL-1000X® machine. They extend out in front of the ServerLIFT® machine, providing ample forward clearance to position the extension attachment hooks and slings over the top of servers in any box - even when the box is on a pallet.

Easy to Use:

- ✓ Attaches to the ServerLIFT® unit with ease no tools or hardware needed
- ✓ Includes extension frame, two slings, four hooks, and storage bag
- ✓ Lightweight yet rigid heavy-duty steel construction











Using the LE-Series Lift Extensions to Remove Servers from Boxes


1 Preparing the server and LE Series Lift Extension


- 1. Insert all four sling hooks into the LE Series Lift Extension.
- 2. Hook loop end of one yellow sling onto rear sling hook on one side.
- 3. Feed loose end of the sling from back to front under the server while server remains in box.
- 4. Hook loose loop end of the sling into the front sling hook on the same side.


5. Repeat with the second sling and sling hooks on the other side.




- 1. Lift equipment out of box and remove packaging.
- 2. Lower equipment down onto a table or secure surface.
- 3. Remove yellow slings from sling hooks.
- 4. Remove slings from under equipment.
- 5. Disengage swing arm, remove Lift Extension from ServerLIFT unit, and safely set aside Lift Extension.
- 6. Slide equipment from table onto ServerLIFT Platform and Easy Glide Shelf.











phone (602) 254-1557 fax (602) 254-1975 Phoenix, AZ 85023

LE Series

DIMENSIONS ARE IN INCHES [SECONDARY DIMENSIONS ARE IN CENTIMETERS]